



**UNIVERSAL BELTING RESOURCE**

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

**2P120/20/0 AS G Green**

**266235**

Thickness (nominal)	3.30 mm	/	0.130 inch
---------------------	---------	---	------------

Weight	4.1 Kg/m <sup>2</sup>	/	0.84 lbs/ft <sup>2</sup>
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	60 mm	/	2.36 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	80 mm	/	3.15 inch

Load for 1% Extension	12 N/mm	/	69 lbs/inch
-----------------------	---------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 <sup>o</sup> to +70 <sup>o</sup> C	/	+14 <sup>o</sup> to +158 <sup>o</sup> F
--	--	---	---

Conveying Surface:	
Material	PVC, approx. 2.0mm
Feature	Gloss
Color	Green
Hardness	75A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Low Noise Monofilament - Cover One Side
----------------------------	---