



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

## 3P120/10/0 AS M White

## 266300

Thickness (nominal) 4.60 mm / 0.181 inch

Weight 5.5 Kg/m<sup>2</sup> / 1.13 lbs/ft<sup>2</sup>

Maximum Width 2000 mm / 78.75 inch

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint) 100 mm / 3.94 inch  
With The Recommended Joint & Reverse Flex Diameter 250 mm / 9.84 inch  
Overlap joint or Fasteners

Load for 1% Extension 12 N/mm / 68 lbs/inch

Standard Tension 0.5 %

Continuous Operating Temperature Range (Product Temp.) -10<sup>0</sup> to +70<sup>0</sup> C / +14<sup>0</sup> to +158<sup>0</sup> F

Conveying Surface:  
Material PVC, approx. 1.0mm  
Feature Matt  
Color White  
Hardness 65A

Underside:  
Material Polyester  
Feature Impregnated  
Color White  
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) 0.25

Recommended Jointing System: Step Splice  
Alternative Splices:  
Finger over Lap  
Finger over Finger  
Finger Splice  
Lace

Anti-Static Yes

FDA Approved Yes

USDA Approved No

Belt Construction Features 3 Ply Monofilament - Cover One Side