



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

3P180/30/0 AS M Green

266301

Thickness (nominal)	6.00 mm	/	0.236 inch
---------------------	---------	---	------------

Weight	7.0 Kg/m <sup>2</sup>	/	1.43 lbs/ft <sup>2</sup>
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	150 mm	/	5.91 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	200 mm	/	7.87 inch

Load for 1% Extension	18 N/mm	/	102 lbs/inch
-----------------------	---------	---	--------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 <sup>o</sup> to +70 <sup>o</sup> C	/	+14 <sup>o</sup> to +158 <sup>o</sup> F
--	--	---	---

Conveying Surface:	
Material	PVC, approx. 3.0mm
Feature	Matt
Color	Green
Hardness	35A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	3 Ply Monofilament - Cover One Side
----------------------------	-------------------------------------