



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P80/05/05 STR AS M Green

266520

Thickness (nominal)	2.60 mm	/	0.102 inch
---------------------	---------	---	------------

Weight	3.0 Kg/m ²	/	0.61 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	50 mm	/	1.97 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	75 mm	/	2.95 inch

Load for 1% Extension	8 N/mm	/	45 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ^o to +70 ^o C	/	+14 ^o to +158 ^o F
--	--	---	---

Conveying Surface:	
Material	PVC, approx. 0.5mm
Feature	Matt
Color	Green
Hardness	85A

Underside:	
Material	PVC, approx. 0.5mm
Feature	Corse Textured Pattern
Color	Green
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.35

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - cover both sides with corse texture bottom. General conveying belt. Medium weight goods. Low-power live roller conveyors, textile machines, wood industry & packaging
----------------------------	--