



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P80/04/04 Matt Blue

266530

Thickness (nominal)	2.40 mm	/	0.094 inch
---------------------	---------	---	------------

Weight	2.9 Kg/m ²	/	0.59 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	50 mm	/	1.97 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	75 mm	/	2.53 inch

Load for 1% Extension	8 N/mm	/	45 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ^o to +70 ^o C	/	+14 ^o to +158 ^o F
--	--	---	---

Conveying Surface:	
Material	PVC, approx. 0.4mm
Feature	Matt
Color	Blue
Hardness	70A

Underside:	
Material	PVC, approx. 0.4mm
Feature	Satin
Color	Blue
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.70

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover Both Sides
----------------------------	---------------------------------------