



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P70/GP/0 AS Green

267110

Thickness (nominal)	3.10 mm	/	0.122 inch
---------------------	---------	---	------------

Weight	3.4 Kg/m ²	/	0.70 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	40 mm	/	1.57 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	60 mm	/	2.36 inch

Load for 1% Extension	7 N/mm	/	40 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ⁰ to +70 ⁰ C	/	-14 ⁰ to +158 ⁰ F
--	--	---	---

Conveying Surface:	
Material	PVC, approx. 1.5mm
Feature	Longitudinal Groove
Color	Green
Hardness	45A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply low noise Monofilament - Cover One Side
----------------------------	---