



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2PL70/LT/0 AS Green

267166

Thickness (nominal)	2.50 mm	/	0.098 inch
---------------------	---------	---	------------

Weight	2.8 Kg/m ²	/	0.57 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	50 mm	/	1.97 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	60 mm	/	2.36 inch

Load for 1% Extension	7 N/mm	/	39 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %		
------------------	-------	--	--

Continuous Operating Temperature Range (Product Temp.)	-10 ^o to +70 ^o C	/	+14 ^o to +158 ^o F
--	--	---	---

Conveying Surface:			
Material	PVC, approx. 1.0mm		
Feature	Lattice		
Color	Green		
Hardness	45A		

Underside:			
Material	Polyester		
Feature	Impregnated		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25		

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Lap Finger Splice Lace
---	---

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Low Noise Monofilament - Cover One Side Lattice Top
----------------------------	--