



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

**2P80/SG/0 AS Green**

**267201**

Thickness (nominal)	4.90 mm / 0.193 inch
---------------------	----------------------

Weight	4.0 Kg/m <sup>2</sup> / 0.82 lbs/ft <sup>2</sup>
--------	--

Maximum Width	2000 mm / 78.75 inch
---------------	----------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	60 mm / 2.36 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	60 mm / 2.36 inch

Load for 1% Extension	8 N/mm / 45 lbs/inch
-----------------------	----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 <sup>o</sup> to +70 <sup>o</sup> C / +14 <sup>o</sup> to +158 <sup>o</sup> F
--	--

Conveying Surface:	
Material	PVC, approx. 1.9mm
Feature	Rough Top
Color	Green
Hardness	45A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side
----------------------------	-------------------------------------