



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

FELT TOP White

290100

Thickness (nominal)	3.40 mm	/	0.133 inch
---------------------	---------	---	------------

Weight	2.8 Kg/m ²	/	0.57 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	60 mm	/	2.36 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	75 mm	/	2.95 inch

Load for 1% Extension	6 N/mm	/	34 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %		
------------------	-------	--	--

Continuous Operating Temperature Range (Product Temp.)	-10 ⁰ to +80 ⁰ C	/	+14 ⁰ to +176 ⁰ F
--	--	---	---

Conveying Surface:			
Material	Polyester Fleece, approx. 1.5mm		
Feature	Non Woven (Fleece) Structure		
Color	White		
Hardness	N/A		

Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		

Recommended Jointing System: Finger over Finger	Alternative Splices: Finger Splice Lace
--	---

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - With Felt Cover
----------------------------	--------------------------------------