

PRODUCT ANNOUNCEMENT

U85 - EX /1E M White

Features

- * Tensile Strength - 23lbs/inch
- * Manufactured Width - 126"
- * Cover Thickness 0.4mm - Double Standard One Plies

Benefits

- * High Density Cover for Easy Cleaning
- * No Edge Curling or Cupping
- * Can Be Spliced Without Foil

**In Stock for Immediate
Delivery**

**REQUEST A
QUOTE TODAY!**

**ITEM # 100123
U85-EX/1E M White
T04 XH M White**

1 Ply Heavy Cover

See complete data sheet on
reverse side

**For Additional information please contact customer service at
customers@ubelting.com or call 800-928-9995**



**#2 Paisley Park
Carmichaels PA 15320
PH: 800-928-9995
FX: 724-966-2452**

**www.universalbelting.com
customers@ubelting.com**



PRODUCT DATA SHEET

U85-EX/1E Matt White

100123

Thickness (nominal)	.8 mm	/	0.031 inch
Weight	.8 Kg/m ²	/	0.16 lbs/ft ²
Maximum Width	3200 mm	/	126 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	8 mm	/	0.31 inch
	16 mm	/	0.63 inch
Load for 1% Extension	4 daN/cm	/	23 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-30 ^o to +80 ^o C / -22 ^o to +176 ^o F		
Conveying Surface:			
Material	Polyurethane		
Feature	Matt		
Color	White		
Underside:			
Material	Polyester		
Feature	PU Impregnation		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	1 Ply monofilament – cover one side		
Recommended Jointing System: Single Finger	Alternative Splices: Skive		
Anti-Static	No		
FDA Approved	Yes		

