

PRODUCT ANNOUNCEMENT ULTRA RELEASE (UR)

Features

- * Ultra Release Cover Compound
- * Easy Splice Procedures
- * Scraper Friendly

Benefits

- * Excellent Product Release
- * Foil Free Splicing
- * Less Product Build-up
- * Less Cleaning Time



100130
U- SI/1 ENF UR Matt White
(T100HR)
1 Ply Non-Fray Fabric



130245
U- SI/2 ENF UR Matt White
(TT12HR)
2 Ply Non-Fray Fabric



110210
U- SI/2 EC UR Matt White
(ST200HR)
2 Ply Spun Fabric

For additional information please contact customer service at
customers@ubelting.com or call **800-928-9995**



#2 Paisley Park
Carmichaels PA 15320
PH: 800-928-9995
FX: 724-966-2452

www.universalbelting.com
customers@ubelting.com



ULTRA RELEASE (UR)

100130 - U-SI/1 ENF UR M White (T100HR)

Thickness	1 mm	(.039 inch)
Weight	1 kg/m ²	(.24 lbs/ft ²)
Minimum Pulley Diameter - Knife Edge	8 mm	(.31 inch)
Minimum Pulley Diameter - Overlap Join	16 mm	(.63 inch)
Load for 1% Extension	3 daN/cm	(17 lbs/inch)
Continuous Operating Temperature	-20 ⁰ to +100 ⁰ C	(-4 ⁰ to +212 ⁰ F)
Anti-Static	NO	
FDA Approved	YES	

130245 - U-SI/2 ENF UR M White (TT12HR)

Thickness	1.8 mm	(.071 inch)
Weight	1.8 kg/m ²	(.37 lbs/ft ²)
Minimum Pulley Diameter - Knife Edge	20 mm	(.8 inch)
Minimum Pulley Diameter - Overlap Join	35 mm	(1.4 inch)
Load for 1% Extension	7 daN/cm	(40 lbs/inch)
Continuous Operating Temperature	-20 ⁰ to +100 ⁰ C	(-4 ⁰ to +212 ⁰ F)
Anti-Static	NO	
FDA Approved	YES	

110210 - U-SI/2 EC UR M White (ST200HR)

Thickness	1.6 mm	(.063 inch)
Weight	1.6 kg/m ²	(.33 lbs/ft ²)
Minimum Pulley Diameter - Knife Edge	10 mm	(.39 inch)
Minimum Pulley Diameter - Overlap Join	25 mm	(1.0 inch)
Load for 1% Extension	6 daN/cm	(34 lbs/inch)
Continuous Operating Temperature	-20 ⁰ to +100 ⁰ C	(-4 ⁰ to +212 ⁰ F)
Anti-Static	NO	
FDA Approved	YES	



#2 Paisley Park
Carmichaels PA 15320
PH: 800-928-9995
FX: 724-966-2452

www.universalbelting.com
customers@ubelting.com

