



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

BF 60E GRAY

351015

Thickness (nominal) 6.00 mm / 0.236 inch

Weight 6.65 Kg/m² / 1.36 lbs/ft²

Maximum Width 500 mm / 19.68 inch

Minimum Pulley or Knife Edge Diameter (With the recommended joint) 70 mm / 2.75 inch

Shaft load Fw at 1% elongation & 180° arc of contact. 20 N/mm / 114 lbs/inch

Maximum tensile load 180 N/mm belt width

Recommended elongation at fitting 0.3 - 2.0%

Continuous Operating Temperature range -20° to +70° C / -4° to +158° F

| | |
|--------------------|----------------|
| Conveying Surface: | |
| Material | G elastomer |
| Feature | Normal Texture |
| Color | Gray |

| | |
|------------|----------------|
| Underside: | |
| Material | G elastomer |
| Feature | Normal Texture |
| Color | Gray |

Belt Construction Features Elastomer with Polyester fabric inner layer

| | |
|---|------------------------------|
| Recommended Jointing System: Finger Splice | Alternative Splices: None |
|---|------------------------------|

Anti-Static Yes

FDA Approved No

Special Features Not sensitive to climatic fluctuation.
Highly abrasion-resistant elastomer coating.