



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

BF 60P GRAY

351115

Thickness (nominal)	6.00 mm	/	0.236 inch
---------------------	---------	---	------------

Weight	6.8 Kg/m ²	/	1.39 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	508 mm	/	20 inch
---------------	--------	---	---------

Minimum Pulley or Knife Edge Diameter (With the recommended joint)	60 mm	/	2.36 inch
---	-------	---	-----------

Shaft load Fw at 1% elongation & 180° arc of contact.	14 N/mm	/	79 lbs/inch
--	---------	---	-------------

Maximum tensile load	350 N/mm belt width		
----------------------	---------------------	--	--

Recommended elongation at fitting	1.5 - 3.0%		
-----------------------------------	------------	--	--

Continuous Operating Temperature range	-20° to +80° C	/	-4° to +176° F
--	----------------	---	----------------

Conveying Surface:			
Material	G elastomer		
Feature	Normal Texture		
Color	Gray		

Underside:			
Material	G elastomer		
Feature	Normal Texture		
Color	Gray		

Belt Construction Features	Elastomer with Nylon sheet inner layer		
----------------------------	--	--	--

Recommended Jointing System: Skive	Alternative Splices: None		
---------------------------------------	------------------------------	--	--

Anti-Static	Yes		
-------------	-----	--	--

FDA Approved	No		
--------------	----	--	--

Special Features	Storage at normal temperature conditions of 23° C/73° F - 50% humidity recommended. Changes in the dimensions possible when conditions do not apply. Good damping properties.		
------------------	--	--	--