



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

PT 37P Green / Black

351133

Thickness (nominal) 3.70 mm / 0.146 inch

Weight 4.0 Kg/m² / 0.82 lbs/ft²

Maximum Width 510 mm / 20.08 inch

Minimum Pulley or Knife Edge Diameter (With the recommended joint) 125 mm / 4.92 inch

Shaft load Fw at 1% elongation & 180° arc of contact. 34 N/mm / 194 lbs/inch

Maximum tensile load 850 N/mm belt width

Recommended elongation at fitting 1.5 - 3.0%

Continuous Operating Temperature range -20° to +80° C / -4° to +176° F

Conveying Surface:	
Material	Rubber
Feature	Fine Top Pattern
Color	Black

Underside:	
Material	Rubber
Feature	Fine Top Pattern
Color	Green

Belt Construction Features Highly Abrasion Resistant Rubber with Nylon Sheet Inner Layer

Recommended Jointing System:	Alternative Splices:
Skive	None

Anti-Static Yes

FDA Approved No

Special Features Suitable for power transmission and spindle drives (black side = spindle side)
 Storage at normal temperature conditions of 20° C/50% humidity recommended