



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

**PT 21 P GR/Black**

**351135**

Thickness (nominal)	2.10 mm	/	0.083 inch
---------------------	---------	---	------------

Weight	2.2 Kg/m <sup>2</sup>	/	0.45 lbs/ft <sup>2</sup>
--------	-----------------------	---	--------------------------

Maximum Width	508 mm	/	20 inch
---------------	--------	---	---------

Minimum Pulley or Knife Edge Diameter (With the recommended joint)	30 mm	/	1.18 inch
---	-------	---	-----------

Shaft load Fw at 1% elongation & 180° arc of contact.	15 N/mm	/	85 lbs/inch
--	---------	---	-------------

Maximum tensile load	350 N/mm belt width		
----------------------	---------------------	--	--

Recommended elongation at fitting	1.5 - 3.0%		
-----------------------------------	------------	--	--

Continuous Operating Temperature range	-20° to +80° C	/	-4° to +176° F
--	----------------	---	----------------

Conveying Surface:	
Material	Highly Abrasion Resistant Rubber
Feature	Super Fine Top Pattern
Color	Black

Underside:	
Material	Highly Abrasion Resistant Rubber
Feature	Fine Top Pattern
Color	Green

Belt Construction Features	Elastomer with Nylon sheet inner layer
----------------------------	--

Recommended Jointing System: Skive	Alternative Splices: None
---------------------------------------	------------------------------

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

Special Features	Suitable for power transmission and spindle drives (black side = spindle side). Storage at normal temperature conditions of 23° C/50% Humidity recommended.
------------------	--