



UNIVERSAL BELTING RESOURCE

1-800-928-9995
customers@ubelting.com

"Working Through Distribution"

PRODUCT DATA SHEET

2P120/10/01 SE Black

200275

Thickness (nominal)	2.5 mm / 0.10 inch
Weight	2.8 Kg/m ² / .58 lbs/ft ²
Maximum Width	2000 mm / 78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint)	60 mm / 2.36 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	120 mm / 4.75 inch
Load for 1% Extension	12 daN/cm / 69 lbs/inch
Standard Tension	0.5 %
Continuous Operating Temperature range	-10 ⁰ to +70 ⁰ C / +14 ⁰ to +158 ⁰ F
Conveying Surface:	
Material	PVC
Feature	Satin
Color	Black
Underside:	
Material	Polyester
Feature	Skim Coat
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2
Belt Construction Features	2 ply multifilament, self-extinguishing
Recommended Jointing System: Overlap	Alternative Splices: Single Finger Finger Over Lap Finger Over Step Lace
Anti-Static	No

