

PRODUCT DATA SHEET

3P180/30/0 S Green

200301

| | | |
|--|--|----------------------------|
| Thickness (nominal) | 6.0 mm | / 0.236 inch |
| Weight | 6.8 Kg/m ² | / 1.39 lbs/ft ² |
| Maximum Width | 2000 mm | / 78.75 inch |
| Minimum Pulley or Knife Edge Diameter (With the recommended joint) | 150 mm | / 6.0 inch |
| With the recommended joint & reverse flex, Overlap joint or Fasteners | 200 mm | / 7.9 inch |
| Load for 1% Extension | 18 daN/cm | / 103 lbs/inch |
| Standard Tension | 0.5 % | |
| Continuous Operating Temperature range | -10 ^o to +70 ^o C / +14 ^o to +158 ^o F | |
| Conveying Surface: | | |
| Material | PVC | |
| Feature | Satin | |
| Color | Green | |
| Underside: | | |
| Material | Polyester | |
| Feature | Bare | |
| Color | White | |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.2 - 0.25 | |
| Belt Construction Features | 3 ply monofilament – cover one side | |
| Recommended Jointing System: | Alternative Spices: | |
| Finger over Finger | Finger Splice Step Splice Lace | |
| Finger over Lap | | |
| | | |
| Anti-Static | Yes | |

