



UNIVERSAL BELTING RESOURCE 1-800-928-9995
 "Working Through Distribution" customers@ubelting.com

PRODUCT DATA SHEET

2P80/0/0 White

200703

Thickness (nominal)	1.4 mm	/ 0.055 inch
Weight	1.6 Kg/m ²	/ 0.33 lbs/ft ²
Maximum Width	3000 mm	/ 118 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint)	20 mm	/ .79 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	20 mm	/ .79 inch
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-20 ^o to +80 ^o C / -4 ^o to +176 ^o F	
Conveying Surface:		
Material	Polyester	
Feature	Bare	
Color	White	
Underside:		
Material	Polyester	
Feature	Bare	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Belt Construction Features	2 ply monofilament, FDA Approved – bare x bare	
Recommended Jointing System: Finger Splice	Alternative Splices: Finger Over Finger Step Splice Lace	
Anti-Static	No	
FDA Approved	Yes	

