

**140205**

**0/2EC-0 PET/Cotton White**

**PVC**

**Material Construction**

Surface	Conveying	Material	Spun Polyester/Cotton
		Profile	Bare
		Color	Beige
		Coefficient of friction	0.2
Tension Member		Material	Spun Polyester/Cotton Fabric
		Plies	2
Underside		Material	Spun Polyester/Cotton
		Profile	Bare
		Color	Beige
		Coefficient of friction	0.20



**Technical Specifications**

Overall Thickness	2.50 mm	0.098 in.
Weight	2.8 kg/m <sup>2</sup>	0.57 lbs./ft <sup>2</sup>
Maximum Width	2,000 mm	78.75 in.
Minimum Pulley/Nose Bar		
Diameter for Recommended Endless Splice	40 mm	1.575 in.
Minimum Back Flex	40 mm	1.575 in.
Load for 1% Extension (Dynamic)	14 N/mm	79.94 lbs./in.
Standard Tension		0.5 %
Product Operational Temperature Range	-7/88 °C	19/190 °F
Cover Durometer	N/A Shore A	

**Material Build**



**Features**

FDA	YES	Anti-Static	NO
USDA Meat and Poultry	NO	Flame Retardant	NO
USDA Dairy	NO	Cross Rigid	SEMI
Anti-Microbial	NO		

**Standard Fabrications**

Longitudinal Splice	YES	Cleats	NO
Guide Applied to Cover	YES	Guide Applied to Bottom	YES
Footed Sidewall	NO	Footless Sidewall	NO
Edge Capped	NO	Plastic Spiral Lace	YES

**Notes**

2 Ply Corse Structured Polyester / Cotton Bare x Bare With PVC Inner Layer. Great For Dough Applications.

\*Minimum pulley diameters can vary when mechanical lace is installed. Contact our technical team for any fabrication or application questions.

**Splicing Instructions**

**High Speed Press Settings**

Pressure (psi)	Temperature		Press Time	Foil Position	Foil	Release Top/Bot.
	Top	Bottom				
20	175°C 347°F	175°C 347°F	90 s	N/A	None	Silicone/ Rough Teflon

**Water Cooled Press Settings**

Pressure (psi)	Temperature		Press Time	Foil Position	Foil	Release Top/Bot.
	Top	Bottom				
20	170°C 338°F	170°C 338°F	30 s	N/A	None	Silicone/ Rough Teflon

\*These settings are a guideline only, every press is different. Test splicing is recommended.

**Standard Splices**

Endless	Finger Over Finger
Clipper Lace	UCM36 SLSP
Staple Lace	RS62

