

266715

2PL130/01/0 Black FR

PVC

Material Construction

Surface	Conveying	Material	Polyester Fabric
	Conveying	Profile	Heavy PU Impregnation
	Conveying	Color	Black
	Conveying	Coefficient of friction	N/A
Tension Member	Material	Polyester Fabric	
	Plies	2	
Underside	Material	Whisper weave polyester	
	Profile	PVC Impregnated	
	Color	Gray	
	Coefficient of friction	0.20	



Technical Specifications

Overall Thickness	1.80 mm	0.071 in.
Weight	2.2 kg/m ²	0.45 lbs./ft ²
Maximum Width	2,000 mm	78.75 in.
Minimum Pulley/Nose Bar		
Diameter for Recommended Endless Splice	36 mm	1.417 in.
Minimum Back Flex	36 mm	1.417 in.
Load for 1% Extension (Dynamic)	13 N/mm	74.23 lbs./in.
Standard Tension		0.5 %
Product Operational Temperature Range	-7/82 °C	19/180 °F
Cover Durometer	N/A Shore A	

Material Build



Features

FDA	NO	Anti-Static	YES
USDA Meat and Poultry	NO	Flame Retardant	YES
USDA Dairy	NO	Cross Rigid	YES
Anti-Microbial	NO		

Standard Fabrications

Longitudinal Splice	YES	Cleats	NO
Guide Applied to Cover	YES	Guide Applied to Bottom	YES
Footed Sidewall	NO	Footless Sidewall	NO
Edge Capped	NO	Plastic Spiral Lace	YES

Notes

Two Ply Flame Retardent with Low noise "Whisper weave" fabric bottom and low friction impregnated top fabric provides for excellent accumulation making it highly suitable for many applications.

*Minimum pulley diameters can vary when mechanical lace is installed. Contact our technical team for any fabrication or application questions.

Splicing Instructions

High Speed Press Settings

Pressure (psi)	Temperature		Press Time	Foil Position	Foil	Release Top/Bot.
	Top	Bottom				
30	175°C 347°F	175°C 347°F	120 s	None	None	Rough Teflon/ Rough Teflon

Water Cooled Press Settings

Pressure (psi)	Temperature		Press Time	Foil Position	Foil	Release Top/Bot.
	Top	Bottom				
30	175°C 347°F	175°C 347°F	30 s	None	None	Rough Teflon/ Rough Teflon

*These settings are a guideline only, every press is different. Test splicing is recommended.

Standard Splices

Endless	Finger Over Finger
Clipper Lace	UCM36 SP
Staple Lace	RS62

