



453150
PS2BLSP55 Blue
PURclean

Material Construction

Composition	Material	TPU-Thermoplastic Polyurethane
	Color	Sky Blue
	Hardness (Shore "A")	90
	Tension Member	TPU Non-Reinforced
Surface Feature	Top	Saw Tooth
	Bottom	Smooth w/ 1" pitch Tooth
COF	Top	0.38
	Bottom	0.38



Material Build



Technical Specifications

Overall Thickness	5.00 mm	0.197 in.
Weight	5.17 kg/m ²	1.06 lbf/ft ²
Maximum Width	914 mm	36 in.
Minimum Pulley/Nose Bar		
Diameter For Endless Butt Splice	51 mm	2.008 in.
Minimum Back Flex	83 mm	3.268 in.
Load For 1% Extension	3.0 N/mm	17.13 lbs/in.
Standard Tension	0.3%	
Operational Temperature Range	-9/71°C	16/160°F

Features

FDA	YES	Anti-Static	NO
USDA Meat and Poultry	YES	Reinforced	NO
USDA Dairy	YES	Elastic	NO

Standard Fabrications

Cleats	NO	Footless Sidewall	NO
Guide on Top	NO	Footed Sidewall	NO
Guide on Bottom	NO		

*Minimum pulley diameters can vary when mechanical lace is installed. Contact our technical team for any fabrication or application questions.

90° Butt Splice Instructions

Standard Amigo Press Settings

*Follow basic Amigo operating instructions

Pre-heat Temperature	Pre-heat Time	Weld Time
95°C	350-355 s	50-55 s

*These settings are a guideline only, every press is different. Test splicing is recommended.

Standard Splices

Butt Splice	Recommended
Soft Hinge Lace	Recommended

Alternative Lace Options

Staple Lace	RS62
Plastic Rivet Lace	APF-150

Notes

Homogeneous urethane construction 1" tooth pitch positive drive bottom with saw tooth profiled top surface for excellent grip properties.