



UNIVERSAL BELTING RESOURCE
Working Through Distribution

DISTRIBUTION ANNOUNCEMENT

**Longitudinal Rib Top
1P40/GP/0 AS BLACK**



**Item # 269100
1P40/GP/0 AS BLACK
“1 ply longitudinal rib top”**

Features

- * Longitudinal profiled top surface
- * Extreme grip low durometer cover
- * 1 ply highly flexible construction
- * Low friction bottom fabric
- * Highly compatible black top finish
- * Neutral product color
- * Rigid lay-flat fabric construction
- * Static dissipating design
- * High quality long lasting top surface
- * Embedded antistatic filaments
- * High strength polyester construction
- * Designed for logistics transport
- * Multiple fabrication options
- * Lightweight - low amp draw

**Proper installation tension required. Contact factory if assistance needed.

Benefits / Applications

- * Low maintenance self cleaning
- * Maintains indexing and induction timing
- * Long life on small transfer rollers
- * Reduced energy costs - greater savings
- * Versatile with wide range of scanners
- * Acceptable with nearly all equipment
- * Avoids edge curl sensor interference
- * Avoid product cling, jams & downtime
- * Reduce frequent replacement costs
- * Protects sensitive equipment & operator
- * No re-tensioning - low maintenance**
- * Field proven performance
- * Spliced, metal or spiral laced, etc.
- * Avoid overload damage & downtime

**For additional information please contact customer service at
customers@ubelting.com or call 800-928-9995**

**www.universalbelting.com
customers@ubelting.com**

**2 Industrial Park Rd
Carmichaels PA 15320
PH: 800-928-9995 FX: 724-966-2452**





UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

1P40/GP/0 AS BLACK 1.6 MM

269100

Overall thickness (Nominal)	1.6 mm / 0.063 inch
Weight	1.50 Kg/m ² / 0.31 Lbs/ft ²
Maximum Width	3000 mm / 118.11 inch
Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	40 mm / 1.58 inch
With The Recommended Joint & Reverse Flex Diameter, Overlap Joint or Fasteners	50 mm / 1.97 inch
Load for 1% Extension	4 N/mm / 22.84 Lbs/inch
Number of Plies	1
Standard Tension	0.5 %
Continuous Operating Temperature Range (Product Temperature)	-10 to 80 °C / 14 to 176 °F
Lateral Construction	Rigid
Conveying Surface:	
Material	PVC
Surface Feature	Longitudinal Rib
Color	Black
Hardness	45
Co-Efficient of Friction (μ)	N/A
	Thickness approximate 0.049 inch
	Shore "A" (On Steel Slide Bed/Drum)
Intermediate layer:	PVC
Underside:	
Material	Polyester Fabric
Surface Feature	Polyester Fabric
Color	White
Hardness	N/A
Co-Efficient of Friction (μ)	0.25
	Thickness approximate N/A inch
	Shore "A" (On Steel Slide Bed/Drum)
Recommended Jointing System:	Alternative Splices:
Finger Spliced	Mechanical Fasteners
Anti-Static	Yes
FDA Approved	No
USDA Dairy	-
USDA Meat & Poultry	-
Belt Construction Features	High grip longitudinal ribbed top cover provides secure and positive transfer while 1 ply construction provides great flexibility with excellent efficiency for significant power savings over two ply counterparts.

PVC Profile Covers