



UNIVERSAL BELTING RESOURCE

Industrial Lightweight Belting

Power Transmission (PT)

Item Number	UBR Number	Description	OAT (mm)	Slab Width (mm)	Shaft Load at 1% (N/mm)	Weight (kg/m ²)	Min Pulley (mm)
351000	BF 30E Gray	Quick Splice	3.00	500	20	3.4	30
351005	BF 40E Gray	Quick Splice	4.00	500	20	4.3	40
351010	BF 50E Gray	Quick Splice	5.00	500	20	5.55	50
351015	BF 60E Gray	Quick Splice	6.00	500	20	6.65	70
351100	BF 30P Gray	Nylon Core	3.00	508	10	3.3	30
351105	BF 40P Gray	Nylon Core	4.00	508	10	4.3	40
351110	BF 50P Gray	Nylon Core	5.00	508	10	5.45	50
351115	BF 60P Gray	Nylon Core	6.00	508	14	6.8	60
351130	PT 32 P Black/Black	Nylon Core	3.20	508	28	3.45	90
351133	PT 37 P Green/Black	Nylon Core	3.70	508	34	4	125
351135	PT 21 P Green/Black	Nylon Core	2.10	508	15	2.2	30
351136	PT 20 P Green/Green	Nylon Core	2.00	508	14	2.1	30
351155	G5/0 XP Green	Nylon Core	1.25	508	6	1.15	24

UBR Power Transmission Range Nomenclature Example

PT 32 P Black/Black

